

# PRP Remote Surveillance Systems

These are new generation CCTV cameras and can be connected directly to your existing LAN/WAN and Wi-Fi Network. They come in several models and can be accessed directly over the Internet. They can also be attached to a NVR (Network Video Recorder) and can employ Intelligent Video Analytics.



## Features

- HTTPS Encryption for enhanced internet security
- Simultaneous Motion JPEG & MPEG-4 Dual Streaming
- Excellent image quality with up to 25 fps in Full D1 resolution
- Supports two-way audio (option).
- Improved quality with de-interlace filter
- UPnP for fast and easy installation
- Bundled 16/32 channel surveillance software
- 2.5G / 3G Mobile Phone Live Viewing
- RTSP Live-viewing Supported (VLC, Quicktime, Real Player, etc...)

## CCD Dome IP Camera

Camera :	1/3" Sharp CCD sensor, 420TVL AGC, AES, AWB Electronic shutter: 1/50 - 1/100000sec (PAL)
Lens :	6.0mm, F1.8
System :	CPU: ARM9 based 32-bit RISC; Flash: 8MB; SDRAM: 64 MB Embedded OS: Linux 2.4
Video Compression :	MPEG-4, Motion JPEG
Video Resolution :	Up to 25 frames at 704x576 (PAL)
Video Streaming :	Simultaneous MPEG-4 & MJPEG (Dual Streaming) Supports Unicast & Multicast Supports 3GPP/ISMA RTSP (Real Time Streaming Protocol)
Audio :	Two-way audio (full duplex)
Alarm and Event :	Built-in multi-window motion detection; Triggered and scheduled events Pre- and Post-alarm buffer; Supports SMTP, FTP and HTTP event
Security :	ID/Password Authentication; SSL Protocol V3.0
Power :	12V DC, 1A, Max 6W
Connectors :	Ethernet – RJ45 for 10/100 Base-T (with PoE); 12V DC; Analog Video Out (BNC) 3.5mm Audio Input, 3.5mm Audio Output
Operating Environment :	0° - 50 °C (32° - 122°F) Humidity 20 - 80% RH (non-condensing)
Surveillance Software:	Surveillance application for viewing, recording and archiving up to 16 cameras
Approvals :	CE, FCC, RoHS