

Speed Dome Camera

Available in Outdoor and Indoor Models. You can move this camera in multi-directions, Left/Right 360°; Up/Down 180°; Zoom In/Out (upto 36x Optical) and can program preset positions. They can be mounted on Ceilings, Walls and Poles and can be connected to a dedicated controller or directly to a Digital Video Recorder. (DVR).



Product Details

Model Name	Speed Dome
Image Device	1/4" Color Sony Super HAD
Picture Elements	PAL:500x582
Resolution	480 TVL
Min. Illumination	0.1 Lux (Night / BW), 0.3 Lux (Day / Color) / F1.6~3.7
Electronic Shutter	PAL:1/50~1/30,000
Lens Furnished	22x (ICR) Auto Focus Zoom (3.9~85.8mm / F1.6~3.7)
Digital Zoom Ratio	Basic 16x (Total Zoom Ratio 352x), 2x~16x variable
Zoom Speed	5 sec
Focus Mode	Auto / Manual / Push Auto
Iris Control	Auto / Manual
White Balance	Auto / Hue / Indoor / Outdoor / manual / Push Auto
Day / Night (ICR)	AE / Sensor / Day / Night
Gain Control	Auto / Manual
Back Light Comp.	On / Off
Pan / Tilt Control Angle	Pan:360°, Tilt:0°~90°
Pan / Tilt Speed Control	Manual: Pan 1°~150° / sec, Tilt 1°~100° / sec Auto: Pan 1°~300° / sec, Tilt 1°~200° / sec
Preset Point	64; 128; 256 preset points
Sequence	6
Controller Interface	RS-485
Compatible Protocol	YOKO / PELCO D&P / LG
On Screen Display	Set-up menu
Auto Turn Around	Yes
Alarm / Relay	6 / 1
Sync. System	Internal
Video Output	1 Vp-p / 75 Ohms
Power Supply	DC12V±10% (option: AC24V)
Power Consumption	DC: 2800mA max. / AC: 2400mA max.
Operating Temp.	-10°C ~ 50°C